



### FRONT DIFFUSER 前面罩

SQAURE TYPE 方形  
DII-3001




RECTANGLE TYPE 長方形  
DII-3002



CROSS FRONT FRAME(+C)  
十字交錯




### DIMENSION 尺寸




### ASYMMETRIC 斜射


SQAURE TYPE 方形  
DII-4001




RECTANGLE TYPE 長方形  
DII-4002



SMOOTH TYPE REFLECTOR(+SR)  
平滑反射罩



### DIMENSION 尺寸



P.6

### APPLICATIONS

CORRIDORS . HALLWAYS . HOTEL ROOMS . PUBLIC AREAS . LOBBIES

### 應用位置

走廊·通道·酒店房間·公眾地方·大堂

### STRUCTURE

**BODY:** SHEET STEEL IN WHITE COLOR AS STANDARD, SILVER(+S) / GREY(+G) / BLACK(+B) ON REQUEST.  
**DIFFUSER:** OPAL DIFFUSER AS STANDARD FOR FRONT DIFFUSER VERSIONS, CLEAR TEMPERED GLASS FOR ASYMMETRIC VERSIONS.  
**CONTROL GEAR:** STANDARD 220V 50HZ SWITCHSTART FOR COMPACT FLUORCESCENT LAMPS, MAGNETIC TRANSFORMER FOR LOW VOLTAGE.

### 結構

燈體：白色標準金屬外殼、另可選擇銀、灰或黑色。  
面罩：奶白色面罩為前置式標準裝配；透明強化玻璃為斜射標準裝配。  
電器：全進口電器（電感／電子／調光電子鎮流器）。

### ORDER CODE 訂購編碼

Cat. No. 型號	Lamp 光源	Dimension 尺寸 (WxLxHmm)	Opening 開口 (WxLmm)
DII-3001-HAL	1x20w (12V) 低壓石英G4	80x80x60	70x70
DII-3001-GLS	1x5w GLS 燈泡E14	80x80x60	70x70
DII-3001-4/9-LED	1w (G/Y/B/W) LED	80x80x60	70x70
DII-3001-207/209-PL	2x7w/9w PL 節能管G23	200x20x100	170x170
DII-3002-107/109/111-PL	1x7w/9w/11w PL 節能管G23	80x500x80	70x490
DII-4001-HAL	1x20w (12V) 低壓石英G4	80x80x60	70x70
DII-4001-GLS	1x5w GLS 燈泡E14	80x80x60	70x70
DII-4001-113-PLC	1x13w PLC 節能管G24d-1	205x205x85	180x165
DII-4002-HAL	1x max. 75w 低壓石英G6.35	130x340x85	125x310
DII-4002-113-PLC	1x13w PLC 節能管G24d-1	205x355x85	180x315