



OPTIC 遮光板
CURVE 弧形

KII-0320/0321




FLAT 平面

KII-0330/0331




REFLECTOR & DIMENSION 反射片及尺寸

SEAGULL WINGS(+SW) 弧底
KII-0320+SW




KII-0330+SW




REFLECTOR & DIMENSION 反射片及尺寸

FLAT SMOOTH(+FS) 平底
KII-0320+FS




KII-0330+FS




PHOTOMETRIC DATA
配光曲線圖

DIRECT & INDIRECT
KII-0320/0330
2x55w PLL



PHOTOMETRIC DATA
配光曲線圖

INDIRECT ONLY
KII-0321/0331
2x55w PLL



APPLICATIONS

LOBBIES . CONFERENCE ROOMS . OFFICE
WITH RECEPTION AREAS . BANK / PUBLIC OFFICES

STRUCTURE

- BOBY:** SHEET STEEL IN STANDARD WHITE POWDER COATED COLOR
- REFLECTOR:** SHEET STEEL IN STANDARD WHITE COLOR AS STANDARD, SPECULAR(+S) / MATT-SATIN(+M) ANODISED ALUMINIUM ON REQUEST.
- LAMP COVER:** 1. INDIRECT-SHEET STEEL IN STANDARD WHITE COLOR AS STANDARD.(CAT.NO. KII-0321/0331)
2. DIRECT-MICROPERFORATED ALUMINIUM IN STANDARD WHITE COLOR AS STANDARD. (KII-0320/0330)
- CONTROL GEAR:** STANDARD IN 220V 50HZ SWITCHSTART(LPF), OTHERS ARE AVAILABLE IN SWITCHSTART HPF(+C) / HF ELECTRONIC BALLAST(+H) / DIMMABLE HF ELECTRONIC BALLAST(+DH).
- EMERGENCY:** REMOTE STANDARD 2 HOURS DISCHARGE NI-CD BATTERY(+REM2), OTHERS ARE AVAILABLE IN 3 HOURS DISCHARGE NI-CD BATTERY(+REM3) / 2 HOURS DISCHARGE NI-MH BATTERY(+REMH2).
- OPTIONS:** FUSED TERMINAL BLOCK(+F).

應用位置

大堂·會議室·辦公室接待處·銀行或大型寫字樓

結構

- 燈體 : 白色粉末噴塑金屬外殼。
- 反光罩 : 白色粉末噴塑鋁反射片或鏡面/啞面鋁。
- 遮光板 : 兩側遮光板用噴白鋁片。
- 電器 : 全進口電器。
- 應急 : 分體應急電池套件。
- 配件 : 可另配保險絲及座。

ORDER CODE 訂購編碼

Cat. No. 型號	Lamp 光源	Dimension 尺寸 (WxLxHmm)
KII-0320/0321/0330/0331-236/240/255 PLL	2x36w/40w/55wPLL 節能光管2G11	600x600x120
KII-0320/0330-214/224 T5	2x14w/24w T5 T5光管G5	600x600x120
KII-0320/0330-218 T8	2x18w T8 T8光管G13	600x650x120
KII-0320/0330-221/239 T5	2x21w/39w T5 T5光管G5	600x900x120
KII-0320/0330-230 T8	2x30w T8 T8光管G13	600x950x120
KII-0320/0330-228/254 T5	2x28w/54w T5 T5光管G5	600x1200x120
KII-0320/0330-236 T8	2x36w T8 T8光管G13	600x1250x120
KII-0320/0330-235/249/280 T5	2x35w/49w/80w T5 T5光管G5	600x1500x120
KII-0320/0330-258 T8	2x58w T8 T8光管G13	600x1550x120
KII-0320/0330-414/424 T5	4x14w/24w T5 T5光管G5	600x600x120
KII-0320/0330-418 T8	4x18w T8 T8光管G13	600x650x120
KII-0320/0330-421/439 T5	4x21w/39w T5 T5光管G5	600x900x120
KII-0320/0330-430 T8	4x30w T8 T8光管G13	600x950x120
KII-0320/0330-440/455 PLL	4x40w/55w PLL 節能光管2G11	600x1200x120
KII-0320/0330-428/454 T5	4x28w/54w T5 T5光管G5	600x1200x120
KII-0320/0330-436 T8	4x36w T8 T8光管G13	600x1250x120
KII-0320/0330-435/449/480 T5	4x35w/49w/80w T5 T5光管G5	600x1500x120
KII-0320/0330-458 T8	4x58w T8 T8光管G13	600x1550x120