



EN60598-1/2    EMERGENCY

HORIZONTAL TYPE (KII-H) 橫插式


IP44



IP54 密封防塵條及不銹鋼螺絲
CONTINUOUS GASKET &
STAINLESS STEEL SCREW




DIMENSION 尺寸




PHOTOMETRIC DATA 配光曲線圖

KII-H-8906/IP44-213
2x13w PLC



VERTICAL TYPE (KII-V) 直插式


IP44



IP54 密封防塵條及不銹鋼螺絲
CONTINUOUS GASKET &
STAINLESS STEEL SCREW




DIMENSION 尺寸



PHOTOMETRIC DATA 配光曲線圖

KII-V-8906/IP54-118
1x18w PLC



APPLICATIONS

LOBBIES . HALLWAYS . LIBRARIES . LIGHTINGS OF SHOPS .
SUPERMARKETS . RESTAURANTS . OFFICES .

STRUCTURE

TRIM + RING:	DIE CAST ALUMINUM IN STANDARD WHITE COLOR, OTHER COLORS ARE AVAILABLE IN BLACK(+B) / SILVER(+S) / GREY(+G) / OTHERS.
HOUSING:	SHEET STEEL IN NATURAL/WHITE COLOR FOR HORIZONTAL TYPE, IN BLACK COLOR FOR VERTICAL TYPE.
REFLECTOR:	ANODIZED ALUMINUM IN STANDARD SPECULAR SILVER, OTHERS ARE AVAILABLE IN DIAMOND FACETED SILVER(+DF) / SATIN SILVER(+SS) / GOLD(+G).
DIFFUSER:	FROSTED TEMPERED GLASS IN STANDARD OTHERS ARE AVAILABLE IN CLEAR(+C) / SEMI-FROSTED(+SF) / DOT PATTERN(+D).
CONTROL GEAR:	STANDARD IN 220V 50HZ SWITCHSTART(LPF), OTHERS ARE AVAILABLE IN SWITCHSTART HPF(+C) / HF ELECTRONIC BALLAST(+H) / DIMMABLE HF ELECTRONIC BALLAST(+DH).
EMERGENCY:	REMOTE STANDARD 2 HOURS DISCHARGE NI-CD BATTERY(+REM2), OTHER ARE AVAILABLE IN 3 HOURS DISCHARGE NI-CD BATTERY(+REM3) / 2 HOURS DISCHARGE NI-MH BATTERY(+REMH2) / 3 HOURS DISCHARGE NI-MH BATTERY(+REMH3).
PROTECTION:	PROTECTIVE FRONT RING + GLASS CAN BE SEALED TO COMPLY WITH THE REQUIREMENT OF IP44, PROTECTIVE FRONT RING + GLASS WITH CONTINUOUS GASKET & STAINLESS STEEL SCREWS CAN BE SEALED TO COMPLY WITH THE REQUIREMENT OF IP54.

應用位置

大堂 · 走道 · 圖書館 · 商舖 · 超級市場 · 餐廳 · 寫字樓 ·

結構

- 內框+外框：白色鑄鋁；
可選擇黑、銀、灰或其他顏色。
- 筒身：直插式為黑色金屬外殼；
橫插式為原色或白色金屬外殼。
- 反光罩：標準鋁電鍍鏡面；
可選擇鑽石琢面、沙銀或金色。
- 面罩：標準強化霜面玻璃；
可選擇透明/半霜面/網紋。
- 電器：全進口電器（電感/電子/調光電子鎮流器）。
- 應急：可配分體 2 小時或 3 小時應急電池套件。
- 保護：保護環+玻璃符合 IP44 標準；
保護環+玻璃符合+膠條及
不銹鋼螺絲符合 IP54 標準。

P.11

ORDER CODE 訂購編碼

IP44 Cat.No. 型號	IP54 Cat.No. 型號	Lamp 光源	Dimension 尺寸(ODxHmm)	Opening 開口(∅mm)
KII-H/V-8905/IP44-GLS	KII-H/V-8905/IP54-GLS	Max. 100w GLS/PAR 燈泡 E27	160x80/150	140
KII-H/V-8905/IP44-110/113	KII-H/V-8905/IP54-110/113	1x10w/13w PLC 節能管 G24d-1	160x80/190	140
KII-H/V-8905/IP44-210/213	KII-H/V-8905/IP54-210/213	2x10w/13w PLC 節能管 G24d-1	160x80/190	140
KII-H/V-8905/IP44-70	KII-H/V-8905/IP54-70	1x70w HIT-DE 高壓金鹵 Rx7s	160x80/150	140
KII-H/V-8906/IP44-GLS	KII-H/V-8906/IP54-GLS	Max. 150w GLS/PAR 燈泡 E27	192x90/170	170
KII-H/V-8906/IP44-113/118/126/132	KII-H/V-8906/IP54-113/118/126/132	1x13w/18w/26w PLC 節能管 G24d-1/2/3	192x90/200	170
		1x32w PLT 節能管 Gx24q-2		
KII-H/V-8906/IP44-213/218/226	KII-H/V-8906/IP54-213/218/226	2x13w/18w/26w PLC 節能管 G24d-1/2/3	192x90/200	170
KII-H/V-8906/IP44-70/150	KII-H/V-8906/IP54-70/150	1x70w/150w HIT-DE 高壓金鹵 Rx7s	192x90/170	170
KII-H/V-8908/IP44-GLS	KII-H/V-8908/IP54-GLS	Max. 250w GLS 燈泡 E40	230x120/200	210
KII-H/V-8908/IP44-113/118/126/132/142	KII-H/V-8908/IP54-113/118/126/132/142	1x13w/18w/26w PLC 節能管 G24d-1/2/3	230x120/230	210
		1x32w/42w PLT 節能管 Gx24q-2/3		
KII-H/V-8908/IP44-213/218/226/232	KII-H/V-8908/IP54-213/216/226/232	2x13w/18w/26w PLC 節能管 G24d-1/2/3	230x120/230	210
		2x32w PLT 節能管 Gx24q-2		
KII-H/V-8908/IP44-70/150	KII-H/V-8908/IP54-70/150	1x70w/150 HIT-DE 高壓金鹵 Rx7s	230x120/200	210