



FIXED BEAM 固定照射

CAT.NO. MI-D313



Lamp MR11 12V20W
Overall Dia. 50mm
Height 40mm
Opening \varnothing 45mm

CAT.NO. MI-D518



Lamp MR16 12V50W
Overall Dia. 80mm
Height 60mm
Opening \varnothing 72mm

CAT.NO. MI-D104



Lamp MR16 12V50W
Overall Dia. 78mm
Height 55mm
Opening \varnothing 60mm

CAT.NO. MI-D058



Lamp MR16 12V50W
Overall Dia. 80mm
Height 60mm
Opening \varnothing 70mm

ADJUSTABLE BEAM 可調節照射

CAT.NO. MI-D091



Lamp MR11 12V35W
Overall Dia. 65mm
Height 45mm
Opening \varnothing 55mm

CAT.NO. MI-D256




Lamp MR16 12V50W
Overall Dia. 95mm
Height 60mm
Opening \varnothing 80mm

CAT.NO. MI-D523



Lamp MR16 12V50W
Overall Dia. 106mm
Height 53mm
Opening \varnothing 93mm

CAT.NO. MI-D524



Lamp MR16 12V50W
Overall Dia. 103mm
Height 55mm
Opening \varnothing 89mm

CAT.NO. MI-D233



Lamp MR16 12V35W
Overall Dia. 110mm
Height 76mm
Opening \varnothing 98mm

P.20

CAT.NO. MI-D028



Lamp MR11 12V50W
Overall Dia. 130mm
Height 65mm
Opening \varnothing 110mm

CAT.NO. MI-D038



Lamp MR16 12V50W
Overall Dia. 160mm
Height 80mm
Opening \varnothing 145mm

CAT.NO. MI-D956



Lamp JC 12V50W
Overall Dia. 90mm
Height 105mm
Opening \varnothing 75mm

NARROW BEAM 窄角度照射

CAT.NO. MI-D5018



Lamp MR16 12V50W
Overall Dia. 88mm
Height 93mm
Opening \varnothing 70mm

CAT.NO. MI-D5019



Lamp MR16 12V50W
Overall Dia. 80mm
Height 60mm
Opening \varnothing 70mm

CAT.NO. MI-D228



Lamp MR16 12V50W
Overall Dia. 135mm
Height 120mm
Opening \varnothing 115mm

FIXED BEAM WITH DIFFUSER (CLEAR/FROSTED TEMPERS GLASS) IP44 防塵固定照射配面罩 (透明/霜面強化玻璃)

CAT.NO. MI-D603



Lamp JC 12V20W-G4
Overall Dia. 70mm
Height 25mm
Opening \varnothing 56mm

CAT.NO. MI-D339



Lamp MR16 12V50W
Overall Dia. 80mm
Height 60mm
Opening \varnothing 70mm

CAT.NO. MI-D957



Lamp JC 12V50W
Overall Dia. 90mm
Height 105mm
Opening \varnothing 75mm

CAT.NO. MI-D954



Lamp JC 12V50W
Overall Dia. 90mm
Height 105mm
Opening \varnothing 75mm

CAT.NO. MI-D239



Lamp MR16 12V50W
Overall Dia. 120mm
Height 90mm
Opening \varnothing 95mm

FIXED BEAM WITH REFLECTOR 固定照射配反光罩

CAT.NO. MI-D506




Lamp JC 12V20W
Overall Dia. 70mm
Height 20mm
Opening \varnothing 56mm

CAT.NO. MI-D240



Lamp MR16 12V50W
Overall Dia. 95mm
Height 67mm
Opening \varnothing 80mm

CAT.NO. MI-D045



Lamp MR16 12V50W
Overall Dia. 115mm
Height 105mm
Opening \varnothing 100mm

CAT.NO. MI-D216



Lamp E14/JC 12V50W
Overall Dia. 125mm
Height 95mm
Opening \varnothing 100mm

CAT.NO. MI-D362



Lamp MR16 12V50W
Overall Dia. 130mm
Height 54mm
Opening \varnothing 115mm

ADJUSTABLE BEAM WITH REFLECTOR 可調較照射配反光罩

CAT.NO. MI-D953




Lamp JC 12V50W
Overall Dia. 90mm
Height 105mm
Opening \varnothing 75mm

CAT.NO. MI-D944




Lamp JC 12V50W
Overall Dia. 90mm
Height 105mm
Opening \varnothing 75mm

CAT.NO. MI-D250



Lamp MR16 12V50W
Overall Dia. 110mm
Height 70mm
Opening \varnothing 90mm





CAT.NO. MI-D071



Lamp JC 12V100W
Overall Dia. 110mm
Height 56mm
Opening \varnothing 85mm

PHOTOMETRIC DATA 配光曲線圖

12V 50W MR16



APPLICATIONS

LIGHTING OF SHOP . SUPERMARKETS . SIGNS . SHELVING (STORES) .
PAINTINGS (MUSEUMS) . WALL LIGHTING .
HIGHLIGHTING OF KEY OBJECT

STRUCTURE

TRIM & BEZEL: DIE CAST ALUMINUM IN STANDARD WHITE COLOR,
BLACK(+B) / CHROME(+C) / BRASS(+R) /
OTHER ARE AVAILABLE.

BODY: DIE CAST ALUMINUM IN NATURAL/WHITE COLOR.

**REFLECTOR /
LOUVER :** ANODISED ALUMINUM IN STANDARD SILVER, GOLD(+G)
/ OTHER ARE AVAILABLE.

DIFFUSER: CLEAR TEMPERED GLASS IN STANDARD, FROSTED(+F) /
DOT PATTERN ARE AVAILABLE.

CONTROL GEAR: REMOTE STANDARD MAGNETIC TRANSFORMER,
HF ELECTRONIC TRANSFORMER(+HT) /
DIMMABLE HF ELECTRONIC TRANSFORMER(+DHT)
ARE AVAILABLE.

EMERGENCY: REMOTE STANDARD 2 HOURS SEALED LEAD ACID
BATTERY(+RE2) & 3 HOURS(+RE3) ARE AVAILABLE.

PROTECTION: WITH GLASS COVER LENS LAMP OR FRONT GLASS
DIFFUSER CAN COMPLY WITH IP44.

應用位置

店舖照明 · 超級市場 · 標示 · 架子 (商店) ·
油畫 (展覽館) · 牆身照明 · 主要物件照射 ·

結構

框邊 : 白色鑄鋁 ;
可選擇黑、鉻、黃銅或其他顏色。

燈體 : 原色或白色鑄鋁外殼。

反光罩 : 標準為鋁電鍍 ;
/百葉 可選擇銀或金色百葉。

面罩 : 強化透明玻璃 ;
可選擇霧面或網紋。

電器 : 全進口分體電器 (電感 / 電子 /
調光電子鎮流器) 。

應急 : 可配分體 2 小時或 3 小時應急套件。

保護 : 配玻璃面蓋或面罩, 符合 IP 4 4 標準。