


EN60598-1/2    EMERGENCY


1-LAMP ROUND
圓形 1 頭



1-LAMP SQUARE
方形 1 頭




2-LAMPS
2 頭




3-LAMPS
3 頭




4-LAMPS
4 頭




4-LAMPS SQUARE
方形 4 頭




6-LAMPS
6 頭



2-LAMPS +
COMPACT FLUO. TUBE
2 頭 + 1 支筷子



4-LAMPS +
COMPACT FLUO. TUBE
4 頭 + 1 支筷子




4-LAMPS +
2-COMPACT FLUO. TUBE
4 頭 + 2 支筷子




DIMENSION 尺寸




1-LAMP ROUND
圓形 1 頭



1-LAMP SQUARE
方形 1 頭



3-LAMP
3 頭



4-LAMPS +
2-COMPACT FLUO. TUBE 4 頭 + 2 支筷子

P.22

APPLICATIONS

LIGHTING OF SHOP . SUPERMARKETS . SIGNS . SHELVING (STORES) .
PAINTINGS (MUSEUMS) . WALL LIGHTING .
LIGHTING OF KEY OBJECT

STRUCTURE

TRIM & BEZEL : DIE CAST ALUMINIUM IN STANDARD WHITE COLOR, OTHER
COLORS ARE AVAILABLE IN BLACK(+B) / SILVER(+S) /
GREY(+G) / OTHERS.

BODY : SHEET STEEL IN STANDARD BLACK COLOR, OTHER COLORS
ARE AVAILABLE.

CONTROL GEAR : STANDARD 230V 50HZ FOR HALOGEN/PAR,
REMOTE STANDARD MAGNETIC TRANSFORMER
FOR LOW VOLTAGE, REMOTE 220V 50HZ SWITCH START
HPF CONTROL GEAR FOR CDM-T,
HF ELECTRONIC TRANSFORMER(+HT) /
HF ELECTRONIC BALLAST(+H) ARE AVAILABLE.

EMERGENCY : REMOTE STANDARD 2 HOURS SEALED LEAD ACID
BATTERY(+RE2) & 3 HOURS(+RE3) IS AVAILABLE FOR LOW
VOLTAGE ONLY.

應用位置

店舖照明 · 超級市場 · 標示 · 架子 (商店) ·
油畫 (展覽館) · 牆身照明 · 主要物件照射 ·

結構

框邊 : 標準白色鑄鋁 ;

可選擇黑、銀、灰或其他顏色。

燈體 : 黑色金屬外殼 ; 可選擇其他顏色。

電器 : 全進口電器 (電感 / 電子 / 調光電子鎮流器)。

應急 : 可配分體 2 小時或 3 小時應急套件。

ORDER CODE 訂購編碼

Cat.No.	型號	Dimension 尺寸 (Ø xH/WxLxHmm)	Opening 開口 (Ø/WxLmm)	Lamp 光源
MII-1003R		142x160	130	1x max.50w 12v QR70/50w 12v MR16/50W halogen/50w PAR20/35w CDMR
MII-1004R		180x220	160	1x max.100w 12v AR111/100w par30/70w CDMR/150w CDMT
MII-1003-1		138x138x185	120x120	1x max.50w 12v QR70/50w 12v MR16/50w halogen/50w PAR 20/35w CDMR
MII-1004-1		196x196x200	182x182	1x max.100w 12v AR111/100w PAR 30/70w CDMR/150w CDMT
MII-1003-2		138x250x185	120x223	2x max.50w 12v QR70/50w 12v MR16/50w halogen/50w PAR 20/35w CDMR
MII-1004-2		196x340x200	180x325	2x max.100w 12v AR111/100w PAR 30/70w CDMR/150w CDMT
MII-1003-3		138x345x185	120x315	3x max.50w 12v QR70/50w 12v MR16/50w halogen/50w PAR 20/35w CDMR
MII-1004-3		196x480x200	180x468	3x max.100w 12v AR111/100w PAR 30/70w CDMR/150w CDMT
MII-1003-4		138x443x185	120x417	4x max.50w 12v QR70/50w 12v MR16/50w halogen/50w PAR 20/35w CDMR
MII-1004-4		196x628x200	180x610	4x max.100w 12v AR111/100w PAR 30/70w CDMR/150w CDMT
MII-1003-4S		250x250x185	235x235	4x max.50w 12v QR70/50w 12v MR16/50w halogen/50w PAR 20/35w CDMR
MII-1004-4S		340x340x200	325x325	4x max.100w 12v AR111/100w PAR 30/70w CDMR/150w CDMT
MII-1003-6		138x646x185	120x622	6x max.50w 12v QR70/50w 12v MR16/50w halogen/50w PAR 20/35w CDMR
MII-1004-6		196x907x200	180x890	6x max.100w 12v AR111/100w PAR 30/70w CDMR/150w CDMT
MII-1003-2-T		138x750x180	112x725	2x max.50w 12v/QR70/50w 12v MR16/50w halogen + 1x36w PLL
MII-1004-2-T		196x814x185	166x784	2x max.100w 12v AR111/100w PAR 30 + 1x36w PLL
MII-1003-4-T		138x995x185	112x970	4x max.50w 12v QR70/50w12v MR16/50w halogen + 1x36w PLL
MII-1004-4-T		196x1128x185	166x1098	4x max.100w 12v AR111/100w PAR 30 + 1x36w PLL
MII-1003-4S-T		250x460x180	223x437	4x max.50w 12v QR70/50w 12v MR16/50w halogen + 2x18w PLL
MII-1004-4S-T		340x630x185	310x600	4x max.100w 12v AR111/100w PAR 30 + 2x18w PLL