





## T8 VERSION



PL-0600/0610(T8)



OPTION WITH PRISMATIC  
DIFFUSER FOR T8 LAMP  
配膠罩





OPTION WITH REFLECTOR +  
WIRE GUARD FOR T8 LAMP  
配反光片及網罩





P.30



OPTION WITH REFLECTOR  
FOR T8 LAMP  
配反光片



OPTION WITH WIREGUARD  
FOR T8 LAMP  
配網罩





OPTION WITH ANGLED  
REFLECTOR FOR T8 LAMP  
配不對稱反光片





## T5 VERSION



PL-0620/0630(T5)





OPTION WITH PRISMATIC  
DIFFUSER FOR T5 LAMP  
配膠罩





OPTION WITH REFLECTOR +  
WIRE GUARD FOR T5 LAMP  
配反光片及網罩




OPTION WITH REFLECTOR  
FOR T5 LAMP  
配反光片



OPTION WITH WIREGUARD  
FOR T5 LAMP  
配網罩




OPTION WITH ANGLED  
REFLECTOR FOR T5 LAMP  
配不對稱反光片




### PHOTOMETRIC DATA 配光曲線圖


SINGLE LAMP  
單管




DOUBLE LAMP  
孖管




SINGLE LAMP  
W/ REFLECTOR  
單管 + 反光片




DOUBLE LAMP  
W/ REFLECTOR  
孖管 + 反光片



SINGLE LAMP  
W/ PRISMATIC  
單管 + 膠罩



DOUBLE LAMP  
W/ PRISMATIC  
孖管 + 膠罩



### APPLICATIONS

INDUSTRIAL OR INSTITUTIONAL PREMISES .  
WORKSHOPS . STORES . SERVICE AREAS

### 應用位置

工廠 · 裝配室 · 商店 · 維修室 ·

### STRUCTURE

- BODY:** SHEET STEEL IN STANDARD WHITE COLOR.
- CONTROL GEAR:** STANDARD IN 220V 50HZ SWITCHSTART(LPF), OTHERS ARE AVAILABLE IN SWITCHSTART HPF(+C) / HF ELECTRONIC BALLAST(+H) / DIMMABLE HF ELECTRONIC BALLAST(+DH).
- EMERGENCY:** STANDARD 2 HOURS DISCHARGE NI-CD BATTERY(+EM2), OTHERS ARE AVAILABLE IN 3 HOURS DISCHARGE NI-CD BATTERY(+EM3) / 2 HOURS DISCHARGE NI-MH BATTERY(+EMH2).
- OPTIONS:** FUSED TERMINAL BLOCK(+F).

### 結構

- 燈體 : 噴白金屬外殼。
- 電器 : 全進口電器(電感式、電子式或調光暗電子式)。
- 應急 : 可配分體2小時/3小時電池套件。
- 配件 : 可配另加保險絲 + 座。

### ACCESSORIES ON REQUEST

- REFLECTOR MADE OF SHEET STEEL THERMOENMALLED IN WHITE AS STANDARD. ANODIZED ALUMINIUM IN SPECULAR(+SRS) OR MATT-SATIN(+SRM) ON REQUEST.
- PRISMATIC DIFFUSER(+AD) MADE OF PMMA AS STANDARD. OPAL DIFFUSER(OD) ON REQUEST.
- WIRE GUARD(+WGW) MADE OF STEEL THERMOENMALLED IN WHITE AS STANDARD. STAINLESS STEEL WIRE GUARD(+WGS) ON REQUEST.
- ANGLED REFLECTOR(+ARW) MADE OF SHEET STEEL THERMOENMALLED IN WHITE AS STANDARD. ANODIZED ALUMINIUM IN SPECULAR(+ARS) OR MATT-SATIN(+ARM) ON REQUEST.

### 另加配件

- 噴白金屬對稱反光片 / 鏡面鋁 / 啞面鋁。
- 稜形膠罩 / 奶白膠罩。
- 噴白不對稱反光片 / 鏡面鋁 / 啞面鋁。
- 噴白金屬不對稱反光片 / 鏡面鋁 / 啞面鋁。

### ORDER CODE 訂購編碼

Cat.No. 型號	Lamp 光源	Nominal Length 長度 (mm)
P11-0600-108 T5	1x8w T5	T5光管G5 315
P11-0620-114/124 T5	1x14w/24w T5	T5光管G5 575
P11-0600-118 T8	1x18w T8	T8光管G13 610
P11-0620-121/139 T5	1x21w/39w T5	T5光管G5 875
P11-0600-130 T8	1x30w T8	T8光管G13 915
P11-0620-128/154 T5	1x28w/54w T5	T5光管G5 1175
P11-0600-136 T8	1x36w T8	T8光管G13 1220
P11-0620-135/149/180 T5	1x35w/49w/80w T5	T5光管G5 1475
P11-0600-158 T8	1x58w T8	T8光管G13 1525
P11-0600-170 T8	1x70w T8	T8光管G13 1830
P11-0630-208 T5	2x8w T5	T5光管G5 315
P11-0630-214/224 T5	2x14w/24w T5	T5光管G5 575
P11-0610-218 T8	2x18w T8	T8光管G13 610
P11-0630-221/239 T5	2x21w/39w T5	T5光管G5 875
P11-0610-230 T8	2x30w T8	T8光管G13 915
P11-0630-228/254 T5	2x28w/54w T5	T5光管G5 1175
P11-0610-236 T8	2x36w T8	T8光管G13 1220
P11-0630-235/249/280 T5	2x35w/49w/80w T5	T5光管G5 1475
P11-0610-258 T8	2x58w T8	T8光管G13 1525
P11-0610-270 T8	2x70w T8	T8光管G13 1830