


STANDARD 標準

RIII-4001/4002/4003/4016 (ROUND, 圓形)




DIMENSION 尺寸

RIII-4001/4002/4003/4016



PHOTOMETRIC DATA 配光曲線圖


1x100w PAR30




RIII-4102 (SQUARE, 方形)



RIII-4102




1x42w PLT




RIII-4202 (RECTANGLE, 長形)



RIII-4202



1x70w HIT



APPLICATIONS

CANOPY . CORRIDORS . OUTDOOR HALLWAYS .
BUILDING ENTRANCE HALLS .

應用位置

屋蓋 · 走道 · 戶外通道 · 大廈入口大堂 ·

STRUCTURE

CORROSION RESISTANT EXTRUDED ALUMINIUM PROFILE.
CORROSION RESISTANT DIE-CAST ALUMINIUM COVER.
STAINLESS STEEL SCREWS.
CLEAR TEMPERED GLASS.
ANODIZED SAND BLASTED ALUMINIUM REFLECTOR.
WEATHER PROOF SILICONE GASKET.
INTEGRAL CONTROL GEAR.
CHROMTIZED SURFACE PRETREATMENT.
POLYESTER POWDER COAT WITH UV STABILIZED COMPONENT.

結構

抗腐蝕鋁型材柱體。
抗腐蝕壓鑄鋁底面蓋。
不銹鋼螺絲。
透明強化玻璃。
銀色氧化鋁反射罩。
防水密封條。
連體全進口電器。
前處理電鍍表面。
抗紫外光粉末噴塗。

AVAILABLE COLOR: BLACK(+B) / DARK GREY(+BG) /
SILVER(+S) / WHITE(+W).

外殼顏色：黑 / 深灰 / 銀 / 白。

ORDER CODE 訂購編碼

Cat.No. 型號	Lamp 光源	Dimension 尺寸 (ØxH/WxLxHmm)
RIII-4001-PAR20	1x50w PAR20 冷射燈 E27	105x135
RIII-4002/4102-PAR30	1x100w PAR30 冷射燈 E27	140x180 / 150x150x250
RIII-4003-PAR38	1x120w PAR38 冷射燈 E27	175x220
RIII-4016-18/26PLC	1x18w/26w PLC 節能管 G24-2/3	175x250
RIII-4016-32/42PLT	1x32w/42w PLT 節能管 G24q-3/4	175x250
RIII-4016/4102-23PLE	1x23w PLE 節能管 E27	175x250 / 150x150x250
RIII-4016/4102-35/70HIT	1x35w/70w HIT 高壓金屬 G12	175x250 / 150x150x250
RIII-4202-70HIT(DE)	1x70w HIT-DE 高壓金屬 Rx7s	110x205x200
RIII-4202-150HAL	1x150w HALOGEN 石英管 R7s	110x205x200