




OLODUM MICRO (OC) 微型



DIMENSION 尺寸



OPTION W/ RAZING COVER (+RC)  
可配多面出光面罩




OLODUM MINI (ON) 小型




DIMENSIONS 尺寸


W/ TRANSFORMER  
連體變壓器



W/O TRANSFORMER  
不含變壓器



OPTION W/ RAZING COVER (+RC)  
可配多面出光面罩




OPTION W/ COLOR FILTERS (+CF)  
可配不同顏色過濾片



OLODUM MIDI (OD) 中型




DIMENSION 尺寸





OPTION W/ ANTI-SLIP GLASS ONLY  
FOR MIDI, STANDARD & MAXI (+ASG)  
可配防滑玻璃  
(只適用於中型、標準及大型)



OPTION W/ PROTECTION GRID ONLY  
FOR MIDI, STANDARD & MAXI (+PG)  
可配網罩  
(只適用於中型、標準及大型)




OLODUM STANDARD (OS) 標準 DIMENSION 尺寸




OPTIONS W/ COVERS 可配透光面罩


MONO LIGHT  
單面光



DOUBLE LIGHT  
雙面光





RAZING LIGHT  
多面光





OPTION W/ GRIDS 可配聚光罩


HONEY GRID (+HG)  
蜜蜂形罩




ANTI-GLARE GRID (+AGG)  
低眩光罩



OLODUM MAXI (OX) 大型




DIMENSION 尺寸



OPTION W/ GRID 可配聚光罩

DRAKLIGHT GRID (+DG)  
聚光罩



### APPLICATIONS

HIGHLIGHTS OF BUILDING · LANDSCAPED AREAS · PATHWAYS ·  
SCULPTURE · ARCHITECTURES ·

### STRUCTURE

BODY MADE OF DIE-CAST ALUMINIUM.  
EXTERNAL HOUSING MADE OF THERMOPLASTIC WITH A SECOND TRIM  
MADE OF PAINTED SATIN ALUMINIUM.  
STAINLESS STEEL FRAME (AISI 316).  
GASKET OF GLASS AND COVER IN SILICONE RUBBER.  
TEMPERED PROTECTION GLASS WITH 10MM THICK.  
INTEGRAL CONTROL GEAR.  
MAXIMUM DEAD LOAD OF 2000KG (NOT FOR MICRO & MINI).  
DRIVE-OVER SPEED OF 25KM/H (ONLY FOR MIDI, STANDARD & MAXI).





















### 應用位置

外牆標誌 · 庭園 · 行人道 · 建築物 ·

### 結構

壓注鋁外殼。  
耐高溫膠筒。  
不銹鋼面框。  
密封膠條。  
強化玻璃。  
可抗重量2000公斤(不適用於微型及小型)。  
汽車時速25公里(只適用於中型、標準及大型)。

### ORDER CODE 訂購編碼

Cat. No. 型號	Lamp 光源	Light Beam 光角度	"T" °C 表面溫度
OC-8393	1x20w 12v 石英膽 G4		170°
OC-8390	1x20w 12v 石英膽 GZ4		170°
ON-8380	max. 1x50w 12v 石英膽 GY6.35		175°
ON-8385	max. 1x50w 12v 石英膽 GU5.3		130°
ON-8386	max. 1x50w 230v 石英膽 GZ10		180°
OD-8355	max. 1x50w 12v 石英膽 GY6.35		165°
OD-8360	1x18w PLT 節能管 Gx24d2		85°
OD-8370	1x60w HAL 石英管 E27		166°
OD-8371	1x75w PAR 30 反射膽 E27		175°
OS-8350	1x18w PLT 節能管 Gx24d2		81°
OS-8360G	1x60w GLS 燈泡 E27		143°
OS-8360E	1x9w PLE 節能膽 E27		53°
OS-8310-35/70/150HIT	1x35w/70w/150w HIT 高壓金鹵 G12		103°/120°/180°
OS-8330	1x60w HAL 石英管 B15d		105°
OS-8375-35/70/150HIT	1x35w/70w/150w HIT 高壓金鹵 G12		130°/150°/210°
OS-8361-35/70/150HIT	1x35w/70w/150w HIT 高壓金鹵 G12		103°/120°/180°
OX-8300-70/150/250HIT	1x70w/150w/250w HIT 高壓金鹵 Rx7s		105°/152°/180°
OX-8303	1x70w HSE 高壓鈉氣 E27		106°
OX-8305-80/125HME	1x80w/125w HME 高壓水銀 E27		108°/140°
OX-8310-70/150/250HIT	1x70w/150w/250w HIT 高壓金鹵 Rx7s		105°/152°/180°
OX-8315-70/150 HIT	1x70w/150w HIT 高壓金鹵 G12		105°/152°

P.52